



Series 4000

An ideal reel for all general air or water applications, the Series 4000 reel incorporates contemporary engineering and manufacturing techniques to give trouble-free performance. Reels are all-steel construction and compact for applications with critical space requirements. All Reelcraft reels have a full flow shaft and swivel to assure maximum product delivery. The standard low pressure hose is for air or water service only. The basic reel without hose can be used for air, oil and water. Consult manufacturer for other products and hoses.

DIMENSIONS

		4000 O	
		In / mm	
	A	12 7/8	327
	B	12 5/8	321
	C	8	203
	D	2 1/2	64
	E	5 3/8	136

Four 5/16 (8mm) diameter mounting holes.

APPLICATIONS

- Work Shop
- Industrial
- Pneumatic Tools
- Chip Blow-off
- Air & Water
- Farm & Ranch
- Tire Stores
- Automotive Dealers
- Electronic Assembly
- Colleges / Universities
- Vegetable Misting
- Aircraft Maintenance
- Woodworking
- Under the Work Bench
- Transmission Shops

MODELS WITH HOSE				HOSE CAPACITY						MODELS WITHOUT HOSE					
LOW PRESSURE AIR/WATER REELS				Maximum Temperature 150° F (65° C) - Reel inlet is 3/8" NPTF (F)											
MODEL	WGT.		PRESSURE		I.D.		O.D.		LGTH		MODEL	WGT.		PRESSURE	
	lbs / kg		psi / bar		in / mm	in / mm	in / mm	in / mm	ft / m		lbs / kg		psi / bar		
4420 OLP	17#	8	300	21	1/4"	6	.500"	13	20'	6	4400 OLP	17#	8	500	35
4425 OLP	19	9	300	21	1/4"	6	.500	13	25	8	4400 OLP	17	8	500	35
4435 OLP	20	10	300	21	1/4"	6	.500	13	35	11	4400 OLP	17	8	500	35
4617 OLP	19	9	300	21	3/8"	10	.640	16	17	5	4600 OLP	17	8	500	35
4625 OLP	22	10	300	21	3/8"	10	.640	16	25	8	4600 OLP	17	8	500	35

Low pressure hose reels furnished standard with PVC hose. Compressed air hoses should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced. See page 39 for inlet hose assemblies and adjustable bumper stops. **See page 38 for optional mounting bases and brackets.**