

# COMPACT ELECTRIC CORD REELS

Series L4000 & L5000

## Electric Cord Reel Features

- Spring retractable with latch
- Compact for critical space requirements
- Engineered for industrial use
- Durable abrasion and corrosion resistant baked on powder coat finish
- Wall, ceiling or bench mount
- All models supplied with cord are complete with 4-5 foot (approx.) pigtail and three-prong plug
- Adjustable cord stop



L 5750 4



L 4545 7  
L 5550 7

L 4035 3  
L 4050 3  
L 4545 3  
L 5550 3

## APPLICATIONS

- Industrial Plants
- Automotive Service Centers
- Tire Stores
- Service Trucks
- Farm & Ranch
- Fleet Maintenance Facilities
- Aircraft Maintenance
- Woodworking
- Work Shops
- Electric Tools
- Transmission Shops

## STYLE #7 - GFCI

The GFCI Receptacle is designed to protect people from the line-to-ground shock hazards which could occur from defective power tools or appliances operating from this device or from down line outlets protected by it.

**The Ground Fault Circuit Interrupter does not protect against short circuits or overloads. This is the function of the fuse or circuit breaker.**

**Caution:** Persons with heart problems or other conditions which make them susceptible to electric shock may still be injured by ground faults on circuits protected by the GFCI receptacle. There is no safety device yet designed that will protect against all hazards or carelessly handled electrical equipment.



## POWER CORD & CABLE REEL SELECTION CHART For indoor non weather tight applications only

Model No.	Accessory	Cord Specifications				VOLTS	AMPS	WGT. lbs / kg
		AWG/mm <sup>2</sup>	No. Cond.	Length ft / m	Type			
L 4035 163 3	Single Receptacle	16 1.33	3	35' 11	SJTO	115	15	22#10
L 4050 163 3	Single Receptacle	16 1.33	3	50 15	SJTO	115	15	26 12
L 4545 123 3	Single Receptacle	12 3.32	3	45 14	SJO	115	15	28 13
L 5550 123 3	Single Receptacle	12 3.32	3	50 15	SO	115	15	47 21
L 5750 103 4	R.V. Plug	10 5.37	3	50 15	SO	115	35	50 23
L 4545 123 7	Duplex Outlet Box W/GFCI (F)	12 3.32	3	45 14	SJO	115	20	29 13
L 5550 123 7	Duplex Outlet Box W/GFCI (F)	12 3.32	3	50 15	SO	115	20	47 21

## REEL SELECTION CHART - REELS WITHOUT CORD OR CABLE For indoor use only

Model No.	Reel Capacities	Reels are without cord				VOLTS	AMPS	Wgt. lbs / kg
		AWG/mm <sup>2</sup>	No. Cond.	Length ft / m	Type			
L 4000	Reel without electric cord	16 1.33	3	50' 15	SJO	115	25	22# 10
L 4100	Reel without electric cord	16 1.33	4	40 12	SJO	115	25	22 10
L 4500	Reel without electric cord	12 3.32	3	45 14	SJO	115	25	21 9
L 5000	Reel without electric cord	10 5.37	3	35 11	SO	115	35	29 13
L 5400	Reel without electric cord	12 3.32	3	35 11	SO	115	25	25 12
L 5500	Reel without electric cord	12 3.32	3	50 15	SO	115	25	34 15
L 5700	Reel without electric cord	10 5.37	3	50 15	SO	115	35	37 17

All models UL listed at 115 Volt 60 HZ single phase only. For indoor use only. See page 38 for optional mounting bases and brackets.